

Relay Card Type RLC 16

FEATURES

- Relay card with screw terminal strip
- 16 relays with change-over contacts
- Relay driver inverter logic (jumper selectable)
- Low contact resistance
- High through power
- Low capacitance
- Live insertion / removal of cards possible
- Conforms to EC standards for EMC



DESCRIPTION

The RLC 16 Relay Card is designed for use in Vibro-Meter's VM 600 series of machinery protection systems and condition and performance monitoring systems. It is an optional card, for use when the 4 relays on the IOC 4T input/output card are insufficient for the application and additional relays are required.

The RLC 16 is installed in the rear of the ABE 04X rack and connects directly to the rack backplane via a single connector.

The RLC 16 contains 16 relays with change-over contacts. Each relay is associated with 3 terminals on a screw terminal strip accessible at the rear of the ABE 04X rack.

The relays are controlled by open-collector drivers under software control. Jumpers on the RLC 16 card allow the selection of relay normally energized (NE) or normally de-energized (NDE).

SPECIFICATIONS

RELAY CHARACTERISTICS

Make	: Siemens
Type	: PE014005
Contact arrangement	: 1 x (NO + NC) contacts/relay
Coil voltage	: 5 V _{DC}
Coil resistance	: 125 Ω ± 10%
Nominal current	: 0.35 A _{DC} / 5 A _{AC}
Nominal voltage	: 300 V _{DC} / 250 V _{AC}
Max. break power without contact protection	: 100 W (1250 VA)
Pick-up / drop-out / bounce time (contact NO)	: Typically 5 / 2 / 1 ms
Test voltage coil - contact	: 4000 V _{AC}
Test voltage open contact	: 1000 V _{AC}
Mechanical life	: 30 x 10 ⁶ operations
Electrical life	: 10 ⁵ operations

ENVIRONMENTAL

Operating	
• <i>Temperature</i>	: -25°C to +65°C (-13°F to +149°F)
• <i>Humidity</i>	: 0 to 90% non-condensing
Storage	
• <i>Temperature</i>	: -40°C to +85°C (-40°F to +185°F)
• <i>Humidity</i>	: 0 to 95% non-condensing
Vibrations and shock	: See general rack specifications

RELAY PCB ASSEMBLY

Presentation	: 16 relay PCB
Relay state	: Normally energized / normally de-energized (jumper selectable)
Power supply	: +5 V _{DC}
Consumption	: 40 mA x 16
Connections	: Screw terminals
Mounting	: Connects to back plane from rear of rack via a connector
Temperature range	: See above relay characteristics
Humidity	: ≤ 95% (RH non-condensing)

PHYSICAL

Height	: 6 U (262 mm, 10.31 in)
Width	: 20.1 mm
Depth	: 125 mm
Weight	: 0.3 kg

ORDERING INFORMATION

To order please specify :

Type	Designation	Ordering Number
RLC 16	Relay Card	
	- Standard version	200-570-000-1Hh
	- Separate circuits in accordance with IEC/CEI 60255-5 standard	200-570-000-2Hh

Note : “Hh” represents the hardware version. “H” increments for major modifications that can affect product interchangeability. “h” increments for minor modifications that have no effect on interchangeability.



In this publication, a dot (.) is used as the decimal separator and thousands are separated by spaces. Example : 12 345.678 90. Although care has been taken to assure the accuracy of the data presented in this publication, we do not assume liability for errors or omissions. We reserve the right to alter any part of this publication without prior notice.

Sales offices

Vibro-Meter has offices in more than 30 countries. For a complete list, please visit our website.

Your local agent

Head office

Vibro-Meter SA
Rte de Moncor 4
P.O. Box
CH-1701 Fribourg
Switzerland

Tel: +41 26 407 11 11
Fax: +41 26 407 13 01

www.vibro-meter.com

